

# STEPHEN FINKEL PHOTOGRAPHY

## Canon A35 Datelux

The Canon A35 was introduced in October 1977. The Canon A35 was Canon's first camera featuring a built-in flash (located on the upper right hand side). This camera is similar to the A35F, only difference is the A35 Datelux had date printing option. This camera had the nickname of "Nighter" in Japan, which refers to the night baseballs games.

### **Specifications:**

Lens: Canon Lens 40mm f/2.8 elements in 4 groups

Focusing: Double image couple rangefinder

Distance Scale: 0.8 1 1.5 2 5 (m) 3 5 7 15 (ft.)

Shutter: Programmed AE Shutter

Exposure: Meter Coupling Range: EV 9 – 17 (ASA f/2.8 with 1/80 sec. – f/20 with 1/320 sec.)

Film Speed: ASA 25 50 100 200 400

Filter Compensation: automatic

Viewfinder: Bright Frame, parallax correction marks, double image rangefinder, date indication (when the date switch is on and film winding is completed, it lights at the first stroke of the shutter release), aperture scale, over and underexposure warning marks and battery check zone

Film Winding: By rotating the 130° single stroke winding level

Film Loading: Multi-slit spool mechanism

Back Cover Opening: with the back cover opening button

Frame Counter Additive type, automatically reset by opening the back cover

Built in Electronic Flash: The CAT (Canon Auto Tuning) system which can meter the proper exposure according to the distance of the subject and charged voltage

Flash Coverage Angle: Covers up to the angle of a 40mm lens

Flashing Intervals: With a new alkaline manganese battery, it takes less than 8 seconds from one flash to the next pilot lamp lighting

Number of flashes: with a new alkaline battery more than 120 times every 30 seconds

Color Temperature: Balanced for daylight, compensated by the exclusive green dispersion panel

Flash Durations: Shorter than 1/1000 second

Pilot Lamp: Located to the left of the viewfinder on the back of the body.

Date imprinting mechanism: the date is set by rotating the dials on the lens barrel while pressing the date lock release button at the bottom of the lens barrel.

Date Switch: ON/OFF switch on the front of the body.

Size: 122 x 75 x 61mm

**Accessories:** Neck strap and camera case, canonet Hood 5, 48mm filters various kinds.

