

# STEPHEN FINKEL PHOTOGRAPHY

## Ricoh RZ 105SF

Ricoh RZ 105SF is a fully automatic 35mm autofocus lens shutter camera with built in zoom lens.

### **Specifications:**

Lens: 38mm f/4.5 105mm f/8.9 zoom lens. 7 elements, 6 groups

Focusing: Multi-Autofocus type with single a facility

Passive Type with auxiliary AF light in dark conditions

Multi-autofocus in 7 spots and 1707 measuring steps. 0.6m (2 ft.) - infinity 1m (3.3ft) – infinity (at panorama mode)

Macro: 1:1/5.7 at 0.6m (2ft) with 105mm position

Shutter: Programmed electronic shutter, 1, 1/2-1/400 sec

Self-timer: Electronic type with LED indicator. Operating delay approx. 10 sec. Double self-timer is possible with continuous shooting mode.

Viewfinder: Real Image Zoom Viewfinder, Panorama Viewfinder Mask appears in Panorama Mode

Exposure Adjustment: Dual SPD photocell. Programmed AE with Automatic Backlight Control Coupling Range EV5.3-15.5 (wide), EV6.3-16.5 (Tele) (ISO 100)

Film Speed: ISO 50-3200. Compatible with DX Code System Non DX Films are set to ISO 100

Film Load/Wind/Rewinding: Ricoh Auto-Load System. Automatic 1<sup>st</sup> Frame Set. Automatic Film Rewind at the end of film. Mid-roll rewind is possible. Back Cover Safety Lock

Exposure Counter: Electronic Additive. Counts down during film rewind

Built-in Flash: Electronic Flash Automatically activates in dim light and backlight modes, auto, red eye reduction, on ,off, slow Synchro, red eye reduction slow Synchro (soft flash at all modes)

Flash range:

	Wide	Telephoto
ISO 100	0.6m-5.2m (2 ft.-17.1 ft.)	0.6m-2.7m (2ft.-8.9ft.)
ISO 400	0.6m-10.5m (2 ft.-34.5ft.)	0.6m-5.3m (2ft.-17.4 ft.)

Flash Recycle Time: About 6 sec.

Other Features: Infinity/ Super Night Mode, Continuous Shooting Mode, Soft Focus Mode, Remote Control possible with optional remote controller, Date Imprinting (Date Version/ except Panorama Mode), Switchable panorama in midroll

Power Source: 6V lithium battery

Dimensions: 132mm (w) x 73mm (H) x 55mm (D)

Weight: 300g without battery

